

Pavi Home

PaviPlay

PaviHome/PaviPlay Installation Instructions

INTRODUCTION

PaviHome/PaviPlay tiles are manufactured using a combination of high performance polymers. PaviHome/PaviPlay are ideal for home fitness areas, recreation rooms, basements, and home offices.

The highest quality of materials and workmanship are employed in the manufacturing process of PaviHome/PaviPlay floor tiles. However, proper installation is required to ensure the correct performance of the floor and is the installer's responsibility.

Kiefer Specialty Flooring, Inc. thoroughly inspects all orders before shipment. However, it is the installer's responsibility to verify the accuracy of the order and to check the materials for damages, defects, and satisfactory color matching prior to the installation. The installer must report any problems to a Kiefer Specialty Flooring, Inc. representative before installation.

Read all instructions carefully before installation.

HANDLING

Room Temperature

Tiles must be site conditioned at room temperature for 72 hours prior to installation. The room temperature during and after the installation must be maintained between 65° and 70° F.

Exposure To Sunlight

Tiles must be protected from direct or intense sunlight during conditioning and installation by restricting light source. Tiles are not recommended for exterior use. Exposure to excessive UV rays can result in fading and/or color variation.

SUBFLOOR PREPARATION

All subfloors must be clean, smooth, flat to within 1/8" in 10ft., and dry. Dust, scale, and loose particles must be removed.

Concrete sub floors must be checked for moisture content.

Do not install tiles over existing resilient or elastic flooring, or concrete floors equipped with a radiant heating system. Remove all resilient or elastic flooring such as carpet before installation.

INSTALLATION

Tools Needed:

- Rubber Hammer
- Cutting Knife
- Cutting Guide

Temperature Control

The floor should be installed at the average temperature in the room—usually between 65° and 70° F. Allow for expansion of the material by providing security margins and use PaviHome Edger at the ends and PaviHome Joiners for rooms larger than 12 feet.

Installing Near Heat Source

Radiators should be a minimum of 20 inches from tiles or should be separated with isolation materials so that the surface of tiles does not exceed 104° F. If tiles are exposed to direct sunlight, windows should be fitted with curtains or blinds so that the surface of tiles does not exceed 104° F.

Installing Heavy Gym Equipment

Use a dolly or wood boards to protect tiles when installing heavy gym equipment.

1. Position Tiles

Tiles must be dry laid prior to installation. Start in the center of the room and position the tiles as shown in the image below. Connect each pair of tiles and press the interlocks down to avoid tripping hazards. We recommend installing tiles with the PaviGym logo orientated in the same direction.*

5	5	4	3	1	3	4	5	5
5	4	3	2	1	2	3	4	5
1	1	1	1	1	1	1	1	1
5	4	3	2	1	2	3	4	5
5	5	4	3	1	3	4	5	5

*For PaviPlay installations, there is no need to consider direction of logo.

2. Fit To Room

Make all final cuts around room's perimeter, alcoves, offsets, and other obstructions by applying the following procedure:

1. Measure.
2. Mark the trim line with a pen.
3. Make a light cut following the marked trim line with a carpet knife.
4. Following the precut line, cut through the whole tile thickness.
5. Finish the floor with PaviHome Edger or other skirting boards made of wood or other materials.

CLEANING & MAINTENANCE

General Cleaning

Sweep floor with broom. Mop with water and a small amount of mild detergent. For best results, dry floor with cloth.

In Case Of Extreme Dirt

Sweep floor with broom. Use a cleaner diluted in water. (Suggested products include Mr. Clean Antibacterial® and Pine-Sol®.) Rinse well with water. Dry with cloth.

Do not sand or use metal brushes that will scratch the floors surface.

FOR YOUR SAFETY

PaviHome/PaviPlay reduces injury risks, but does not eliminate them. Proper assembly and usage are required for optimum performance. Always use caution when practicing sports. Kiefer Specialty Flooring, Inc. is not responsible for any injuries.